

**PATENT APPLICATION**

**ATTORNEY DOCKET NO.: KCX-518B (17507B)**

UNITED STATES PATENT APPLICATION

for

SURGICAL KIT WITH MULTIPLE PLANAR RECESS SURFACES

of

DONALD J. McMICHAEL

MARK E. FOSTER

**PATENT APPLICATION**

**ATTORNEY DOCKET NO.: KCX-518B (17507B)**

**TITLE OF THE INVENTION**

**SURGICAL KIT WITH MULTIPLE PLANAR RECESS SURFACES**

5

**BACKGROUND**

The present invention relates to pre-packaged surgical kits in general, and more particularly to surgical kits for percutaneous endoscopic procedures.

Various medical procedures are simplified by providing the physician with a kit that contains the majority, if not all, of the necessary medical articles that the physician will need to complete a particular procedure. Kits may include articles such as, for example, drapes, syringes, scalpels, needles, clamps, gauze, sponges, drugs, sutures, and devices. Such kits are commonly provided for procedures such as, for example, percutaneous endoscopic gastrostomy ("PEG") and laparoscopic jejunostomy. These kits reduce the time spent by hospital personnel gathering the appropriate articles that are required for a particular procedure and ensure that the surgeon has each article at hand at the appropriate point in the procedure.

While many current surgical kits include the necessary medical implements or articles to complete a particular procedure, the articles in such kits may not be arranged in the most effective and efficient manner within the kits.

Also, conventional kits provide not only the surgical implements, such as scalpels, needles, scissors, and the like, but also "accessory" items such as swabs, gauze pads, single-use packages of ointments and lubricants, suture

strands, sponges, and the like. These relatively small, loose, items are, however, relatively difficult to store in the kits. Such items may be simply placed loosely in the kit or provided in a sealed pouch. Once the kits or pouches are opened, these items tend to clutter the kit or are moved out of the kit to various locations

5 by the surgical staff. It is difficult to maintain accountability of the items. Also, the accessory items are generally single-use disposable items and conventional kits do not provide a means for accountability and disposal of the devices after use.

### SUMMARY

10 Objects and advantages of the invention will be set forth in part in the following description, or may be obvious from the description, or may be learned through practice of the invention.

The present invention provides a surgical kit of the type wherein the contents of the kit include surgical articles and accessory items to be used in

15 performing a particular type of surgery. An example of such a kit is a percutaneous endoscopic gastrostomy (PEG) kit. It should be appreciated, however, that kits according to the present invention are not limited to any particular set of contents or any particular surgical procedure. The teachings of the present invention are beneficial for any pre-packaged surgical kit.

20 An embodiment of a surgical kit according to the invention includes a tray having a plurality of recesses formed therein for receiving surgical articles or implements useful in performing a particular surgical procedure. The terms surgical "articles" or "implements" are intended to encompass any combination of

devices used in a surgical procedure and may include, without limitation, scissors, clamps, forceps, medicines and drugs, syringes, needles, tubes, scalpels, snares, cannulas, and so forth. Particular types of procedures require specific surgical articles, as is well understood by those skilled in the art. For example, a PEG kit may also include a "push" or "pull" assembly, a bolus adapter assembly, locking ring, snare device, etc.

The kit may also include any combination of "accessory" surgical items. The term "accessory" item is meant to encompass generally loose ancillary articles such as any number of pre-packaged single-use disposable items. Such items may include, for example, sutures, swabs, ointment packages, lubricant packages, drapes, gauze pads, small vials or packages of drugs, and the like. In this regard, the kit according to the invention may include an accessory item container received in a container recess defined in the tray. The accessory items may be placed in a separate container which is then placed in the tray prior to sealing the tray. The container may be seated in a respective recess defined in the tray.

The tray generally includes a cover that is sealed thereto, for example by an adhesive around a peripheral edge of the tray. In order to gain access to the contents of the tray, the cover is peeled or removed from the tray.

The tray includes a plurality of planar surfaces formed therein. The plurality of recesses are defined in the planar surfaces. The planar surfaces are offset vertically such that each planar surface is offset with respect to at least one other planar surface. In this manner, unobstructed access to certain of the

recesses in at least one of the lower planar surfaces is obtained by removing articles from recesses in at least one upper planar surface. In particular embodiments, a first planar surface, a second planar surface and a third planar surface may be provided in the tray. The second planar surface may be offset from the first planar surface. The third planar surface may be offset from the first planar surface.

A particular embodiment of a surgical kit according to the invention is a PEG kit wherein each recess is adapted to hold an article that is useful in performing a percutaneous endoscopic gastrostomy. At least one of the recesses may be adapted to retain at least a portion of a percutaneous endoscopic gastrostomy tube. In some embodiments, such a recess may be disposed on the second planar surface. A retrieval snare and/or a guide wire may be positioned over at least a portion of the percutaneous endoscopic gastrostomy tube. One of the recesses may be adapted to retain a looped placement wire. In particular embodiments, such a recess may be disposed on the first surface. One of the recesses may be adapted to retain an exterior tube retention device, and such a recess may be disposed on the second planar surface in some embodiments. Another of the recesses may be adapted to retain an introducer cannula, and such a recess may be disposed in the third planar surface.

Some of the planar surfaces may have one or more bosses extending upwardly therefrom. In some embodiments, at least one boss may extend upwardly from the second planar surface. At least one boss may be disposed

upon the first planar surface. An article may be positioned so that at least a portion of such an article is disposed about a boss.

The invention will be explained below in further detail by way of reference to an embodiment of the invention illustrated in the figures.

5

### **BRIEF DESCRIPTION OF THE FIGURES**

Figure 1 is a perspective component view of an embodiment of a surgical kit according to the present invention.

Figure 2 is a top plan view of the embodiment shown in Figure 1 with the articles placed in their respective recesses.

10

Figure 3 is a perspective component view of an embodiment of the container according to the invention having been removed from the tray.

Figure 4 is a perspective view of an embodiment of a tray and stored articles, including the container.

15

Figure 5 is a perspective view of the tray according to Fig. 4 without the articles contained therein.

Figure 6 is a top plan view of the tray according to Fig. 5.

Figure 7 is a side view of the tray according to Fig. 5.

Figure 8 is an end view of the tray according to Fig. 5.

### **DETAILED DESCRIPTION**

20

Reference will now be made in detail to embodiments of the invention, one or more examples of which are illustrated in the figures. The embodiments are provided by way of explanation of the invention, and not meant as a limitation of the invention. For example, features illustrated or described as part of one

embodiment may be used with another embodiment to yield still a different embodiment. It is intended that the invention include these and other modifications as come within the scope and spirit of the invention.

An embodiment of a surgical kit is illustrated in the figures as a

5 percutaneous endoscopic gastrostomy ("PEG") kit 20. It should be understood that a PEG kit is illustrated and described herein as merely representative of an embodiment of a surgical kit according to the invention, and that the invention is not limited to a PEG kit or any other particular type of kit. A PEG procedure is utilized to place a feeding tube into a patient that extends from the interior of the

10 patient's stomach exteriorly of the patient. The feeding tube permits nutrients to be placed directly into a patient's stomach. This may be necessary when a patient has a disorder of the gastrointestinal tract, malabsorption (impaired absorption of nutrients, vitamins or minerals from the diet by the lining of the small intestine), or neurological or renal disorders. The feeding tube inserted

15 using a PEG procedure is kept in place until a stoma is formed. Once a stoma is formed, a patient may remove and replace the PEG feeding tube with an alternate feeding device.

The PEG kit 20 may include a tray 22 having a plurality of planar surfaces and a plurality of recesses that may be disposed within the planar surfaces. The

20 tray 22 may be formed of any suitable material, for example the tray 22 may be molded from a transparent or translucent substantially rigid plastic material (i.e., PETG). The tray 22 may have side walls 23 defining a depth of the tray 22.

As described in more detail below, the planar surfaces may be vertically offset within the tray 22. For example, referring to Figs. 1, 5, and 6, a plurality of substantially horizontal planar surfaces 64, 66, 68, and 70 are defined in the tray 22. The planar surfaces may be co-molded with the tray 22. Each of the planar surfaces is vertically offset within the tray 22 with respect to at least one other planar surface.

A plurality of recesses adapted to hold articles or implements that are useful in performing the intended surgical procedure are defined in the various planar surfaces 64, 66, 68, and 70. Each recess may be adapted to hold one or more articles. Examples of recess configurations and respective articles held therein are discussed in greater detail below. The recesses may also include detents, protrusions, or the like to frictionally engage and retain the articles within the respective recesses.

As seen in Figure 1, a cover 26 may be positioned on the tray 22 and, in some embodiments, may be adhered to a relatively flat peripheral surface 28 of the tray 22. A corner 30 of the tray 22 may be configured so that the cover 26 is not adhered to the corner 30. In such an embodiment, a user may grasp the cover 26 that is positioned adjacent to the corner 30 to remove the cover 26 from the tray 22. The cover may be attached to the tray by any suitable method, including but not limited to adhesives, heat sealing, sonic or thermal welding, solvents, etc. Once all of the articles have been placed into the tray 22 and the cover sealed to the tray, the kit is subjected to ETO gas sterilization.



A suitable cover material is Tyvek™, a spunbond polyolefin, from DuPont of Wilmington, Delaware. Any number of other permeable web materials suitable for ETO (ethylene oxide) gas sterilization, such as Kraft paper, may be used as the cover 26.

5 As illustrated generally in the figures, a container 24 is provided with the kit 20. The container is desirably a substantially rigid structure adapted to fit at least partially within the tray 22. For example, the container 24 may rest upon the planar surface 64. Desirably, the container 24 is disposed generally at the top of the tray so that access is provided to the container 24 immediately upon  
10 removing the cover 26 from the tray 22. In this way, the container 24 can be the first item removed from the tray 22 without touching or displacing any of the other articles in the tray 22. The tray side walls 23 and a bumper wall 126 define a recess or nesting place for the container and engage or retain the container 24 in a precise location within the tray 22. In one embodiment, the container 24 may  
15 be press-fitted into the nesting place. In another embodiment, the container 24 may be loosely received into the nesting place.

Figure 3 illustrates an embodiment of a container 24 that may be used in the present invention. The container 24 may include a substantially rigid lid 34 and a base 36, the lid 24 and the base 36 being flexibly attached to each other  
20 by a hinge 38 (i.e., a living hinge). In some embodiments, the lid 34 and the base 36 may not be attached to each other, or may be attached to each other using alternate configurations. The container may be molded or otherwise formed from the same polymer material as the tray 22. A lip 40 may be provided

that extends around the edges of the lid 34 and the base 36. In particular embodiments, an extended portion 42 may be disposed along one edge of the lip 40 to enable a user to more easily open the container 24. One or both of the lips 40 may include a number of bosses 41 extending therefrom. These bosses 41

5 keep the opposing lips 40 spaced apart in a closed state of the container so that the ETO (ethylene oxide) sterilization gas can readily permeate into the container.

The container 24 is desirably configured to be reclosable. In this manner, the container 24 provides a convenient device for storing used articles prior to

10 disposal. The container 24 may be variously configured so that it is reclosable by, for example, providing a pair of bosses 44 disposed on the lid 34 that mate to a pair of detents 46 that are disposed on the base 36. Other mechanisms that may be useful to reclose the container 24 include but are not limited to

adhesives, hook-and-loop fasteners, locking arms, and the like.

15        Embossing, such as embossing 52 in Figure 3, may be disposed on the outer surface 48 of the lid 34 or on the outer surface 50 of the base 36. Alphanumeric, numeric or other characters may be embossed on the container 24.

The tray 22 and container 24 are illustrated as generally rectangular in the

20 figures. However, it should be appreciated that these components may take on any convenient shape.

Referring to Fig. 3, the container 24 may be adapted to hold a variety of accessory medical articles including, for example, suture strands (packaged)

112A, swabs (i.e., povidone-iodine prep swabsticks) 124A, lidocaine insert 122A, fenestrated gauze pads 108A, gauze pads 108B, fenestrated drape 129A, single-use packages of lubricant 130A, single-use packages of ointment 124B (i.e., povidone-iodine ointment), antibiotic ointment 128A, sponges, and the like.

5 As described, the container is particularly well suited for retaining these devices after they have been used for later disposal.

As shown in the Figures in general, the tray 22 may include a first planar surface 64. Several recesses are disposed in surface 64, including two recesses 76 that may be used to hold or support coiled articles and a needle recess 81.

- 10 The recesses 76 can be seen particularly in Figs. 5 and 6 and may be, for example, generally circumferentially extending recesses that extend around at least a portion of a generally circular structure that defines planar surface 68, as described in greater detail below. The needle recess 81 may include two elongated recesses 80 and 82 so that the needle recess 81 may hold two
- 15 needles securely. In selected embodiments, recess 80 may be configured to hold a filter needle 80A and the recess 82 may be configured to hold a needle 82A. A recess 90 may be disposed in the first surface 64 and may be configured to hold a looped placement wire 90A for "pull" type PEG procedures. In some
- 20 the recess 90 may be rounded to easily accept and hold the looped placement wire 90A.

The first surface 64 may also include a recess 103 that may be configured to have elongated portions 104 and 105. A pair of surgical scissors 104A may be

disposed in the portion 104 of the recess 103, and a hemostat 105A may be disposed in the portion 105 of the recess 103.

The first surface 64 may also include a recess 115 that may be elongated and have two spaced apart ends 114 and 116. As shown in Figures 1 and 2, a  
 5 bolus feeding adapter 114A may be at least partially disposed in the end 114 of the recess 115. A universal feeding adapter 116A may also be at least partially disposed in the end 116 of the recess 115.

The first planar surface in the illustrated embodiment also defines a nesting place for the container 24. An elongated boss 126 may be disposed on  
 10 the first planar surface 64 for this purpose. This boss 126 and two of the tray side walls 23 cooperate to define a recess or storage location for the container 24 on the first planar surface 64. The container 24 actually rests on the surface 64 above a number of the article recesses. For example, referring to Figs. 1, 5, and  
 15 6 the recesses 80, 81, 82, 90, 103, 104, and 105, as well as their associated articles, are all disposed under the container 24. The physician must first remove the container 24 to gain access to these recesses.

As seen in Figures 4-6, a second planar surface 66 may also be provided and may, in selected embodiments, be offset from the first planar surface 64. Numerous recesses may be disposed in the second planar surface 66 including  
 20 a recess 78 that is adapted to hold a container of lidocaine 78A and a recess 84 that may be adapted to hold a scalpel 84A, as shown in Figure 4.

A recess 110 may also be provided in the second planar surface 66, the recess 110 being adapted to hold an exterior tube retention device 110A. In

some embodiments, a SECUR-LOK™ ring, available from Ballard Medical Products in Draper, Utah, may be used as an exterior tube retention device 110A. A boss 132 may be disposed in the recess 110 to support the exterior tube retention device 110A.

- 5           The second planar surface 66 may also include a recess 94 that is adapted to hold at least a portion of a percutaneous endoscopic gastrostomy (PEG) tube 94A, as seen in Figure 1. Such a PEG tube typically includes an internal retention device such as a bumper 98A and an elongated tube 96A. For a "pull" type PEG procedure, a loop is provided at the end of the tube 96A. For a
- 10 "push" type of PEG procedure, an elongated tapered tip 100A is provided at the end of the tube 96A. The recess 94 may include a rounded portion 98 that will hold the bumper 98A. The recess 94 may also include an elongated portion 96 that will hold at least a portion of the elongated tube 96A. The portion of the elongated tube 96A that is not disposed in the elongated portion 96 of the recess
- 15 94 may be coiled and placed within the recesses 76 that are formed in the first planar surface 64. In such an embodiment, a portion of the coiled elongated tube 96A may rest on the portions of the first planar surface 64 that are disposed between the recesses 76.

- One or more bosses 92 may be disposed on the second planar surface
- 20 proximate to the recess 94, one boss 92 being disposed on one side of the recess 94 and another boss 92 being disposed on the other side of the recess 94. In such an embodiment, a retrieval snare 92A, as seen in Figure 4, may be positioned on the second planar surface so that the handle 91A of the retrieval

snare 92A is secured in place by the bosses 92. In such an embodiment, at least a portion of the retrieval snare 92A is positioned over the PEG tube 94A, the bumper 98A being disposed under the handle 91A of the retrieval snare 92A. The coiled end 93A of the retrieval snare 92A may be disposed over a portion of the coiled tube 96A of the PEG tube 94A so that both coils 93A and 96A supported by the first planar surface 64 and may be at least partially disposed in the recesses 76.

For "push" type PEG procedures, a coiled sheathed guide wire 106A may be provided in the kit, as seen in Figs. 1, 2, and 6. The guide wire 106A may be placed in the recess 76 on top of the coiled end of the snare 93A and coiled tube 96A of the PEG tube 94A.

A third planar surface 68 may also be provided in the tray 22. The third planar surface may be offset from the first planar surface 64, from the second planar surface 66, or from both the first and second planar surfaces 64 and 66, respectively. In the embodiment depicted in the Figures, the third planar surface 68 may be disposed within the interior of the coils 93A and 96A. A recess 120 may be formed in the third planar surface as shown in Figure 9. The recess 120 may be configured to hold one or two twelve-ounce syringes 120A. A recess 118 may also be disposed in the third planar surface 68 and may be adapted to hold a tubing clamp 118A.

A fourth planar surface 70 may be disposed adjacent to the third planar surface 68, as seen in Figures 4 and 5. A recess 86 that is adapted to hold an

introducer cannula 86A may be formed in the third and fourth planar surfaces 68 and 70, respectively.

In selected embodiments and as shown in Figure 5, a fifth planar surface 72 may be provided that is adjacent to the fourth planar surface 70. The fifth planar surface 72 may be configured to provide additional support to the coils 93A and 96A.

The tray 22 may also be configured to hold a pamphlet (not shown) that may contain various information such as, for example, directions for using the PEG kit 20.

- 10 From the foregoing description, it should be appreciated that the arrangement of the vertically offset planar surfaces and their respective article recesses results in an arrangement wherein certain of the articles must be removed from the kit before unobstructed access is provided to certain underlying articles. The articles are arranged so that, desirably, such articles can
- 15 be readily removed from the tray in their order of use. For example, in the embodiment illustrated in the Figures wherein the surgical kit is a PEG kit, the container 24 contains many of accessory items needed to prep the surgical site on the patient. The container is seated in its recess on the first planar surface 64 and is readily removable upon removing the cover 26 from the tray 22. The
- 20 snare device 92A within recess 92 is used before the PEG tube 94A within recess 94, and the snare device 92A must be removed before the PEG tube 94A can be removed. The feeding adapters 114A and 116A within respective

recesses 114 and 116 are used towards the end of a PEG procedure and access to the adapters is provided after removal of the snare 92A and PEG tube 94A.

The invention may be embodied in other specific forms without departing from the scope and spirit of the inventive characteristics thereof. The present  
 5 embodiments therefore are to be considered in all respects as illustrative and not restrictive, the scope of the invention being indicated by the appended claims rather than by the foregoing description, and all changes which come within the meaning and range of equivalency of the claims are therefore intended to be embraced therein.

114  
 116  
 118  
 120  
 122  
 124  
 126  
 128  
 130  
 132  
 134  
 136  
 138  
 140  
 142  
 144  
 146  
 148  
 150  
 152  
 154  
 156  
 158  
 160  
 162  
 164  
 166  
 168  
 170  
 172  
 174  
 176  
 178  
 180  
 182  
 184  
 186  
 188  
 190  
 192  
 194  
 196  
 198  
 200  
 202  
 204  
 206  
 208  
 210  
 212  
 214  
 216  
 218  
 220  
 222  
 224  
 226  
 228  
 230  
 232  
 234  
 236  
 238  
 240  
 242  
 244  
 246  
 248  
 250  
 252  
 254  
 256  
 258  
 260  
 262  
 264  
 266  
 268  
 270  
 272  
 274  
 276  
 278  
 280  
 282  
 284  
 286  
 288  
 290  
 292  
 294  
 296  
 298  
 300  
 302  
 304  
 306  
 308  
 310  
 312  
 314  
 316  
 318  
 320  
 322  
 324  
 326  
 328  
 330  
 332  
 334  
 336  
 338  
 340  
 342  
 344  
 346  
 348  
 350  
 352  
 354  
 356  
 358  
 360  
 362  
 364  
 366  
 368  
 370  
 372  
 374  
 376  
 378  
 380  
 382  
 384  
 386  
 388  
 390  
 392  
 394  
 396  
 398  
 400  
 402  
 404  
 406  
 408  
 410  
 412  
 414  
 416  
 418  
 420  
 422  
 424  
 426  
 428  
 430  
 432  
 434  
 436  
 438  
 440  
 442  
 444  
 446  
 448  
 450  
 452  
 454  
 456  
 458  
 460  
 462  
 464  
 466  
 468  
 470  
 472  
 474  
 476  
 478  
 480  
 482  
 484  
 486  
 488  
 490  
 492  
 494  
 496  
 498  
 500  
 502  
 504  
 506  
 508  
 510  
 512  
 514  
 516  
 518  
 520  
 522  
 524  
 526  
 528  
 530  
 532  
 534  
 536  
 538  
 540  
 542  
 544  
 546  
 548  
 550  
 552  
 554  
 556  
 558  
 560  
 562  
 564  
 566  
 568  
 570  
 572  
 574  
 576  
 578  
 580  
 582  
 584  
 586  
 588  
 590  
 592  
 594  
 596  
 598  
 600  
 602  
 604  
 606  
 608  
 610  
 612  
 614  
 616  
 618  
 620  
 622  
 624  
 626  
 628  
 630  
 632  
 634  
 636  
 638  
 640  
 642  
 644  
 646  
 648  
 650  
 652  
 654  
 656  
 658  
 660  
 662  
 664  
 666  
 668  
 670  
 672  
 674  
 676  
 678  
 680  
 682  
 684  
 686  
 688  
 690  
 692  
 694  
 696  
 698  
 700  
 702  
 704  
 706  
 708  
 710  
 712  
 714  
 716  
 718  
 720  
 722  
 724  
 726  
 728  
 730  
 732  
 734  
 736  
 738  
 740  
 742  
 744  
 746  
 748  
 750  
 752  
 754  
 756  
 758  
 760  
 762  
 764  
 766  
 768  
 770  
 772  
 774  
 776  
 778  
 780  
 782  
 784  
 786  
 788  
 790  
 792  
 794  
 796  
 798  
 800  
 802  
 804  
 806  
 808  
 810  
 812  
 814  
 816  
 818  
 820  
 822  
 824  
 826  
 828  
 830  
 832  
 834  
 836  
 838  
 840  
 842  
 844  
 846  
 848  
 850  
 852  
 854  
 856  
 858  
 860  
 862  
 864  
 866  
 868  
 870  
 872  
 874  
 876  
 878  
 880  
 882  
 884  
 886  
 888  
 890  
 892  
 894  
 896  
 898  
 900  
 902  
 904  
 906  
 908  
 910  
 912  
 914  
 916  
 918  
 920  
 922  
 924  
 926  
 928  
 930  
 932  
 934  
 936  
 938  
 940  
 942  
 944  
 946  
 948  
 950  
 952  
 954  
 956  
 958  
 960  
 962  
 964  
 966  
 968  
 970  
 972  
 974  
 976  
 978  
 980  
 982  
 984  
 986  
 988  
 990  
 992  
 994  
 996  
 998  
 1000